



## **bizhub® 308e**

### MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER

- Up to 30 ppm print/copy output to keep pace with rising demands
- Optional dual scanning up to 160 originals per minute
- Large 9" color display with quick tablet-like touchscreen interface
- 3rd-party software integration with standard web browser
- Built-in Emperon® print system, universal printer drivers
- Simitri® HD polymerized toner for high-resolution imaging
- Standard 250 GB HDD for on-board document storage
- Meets ISO 15408 and IEEE 2600.1 Security standards\*
- Standard web browser
- Power-saving design with quick recovery from sleep mode

- 6,650-sheet maximum capacity, tab printing support, carbon-copy printing
- Advanced authentication, secure print release, remote firmware updates
- Multiple bypass tray and detachable paper feed trays improve paper handling
- Finishing options for 80-page booklet-making, up to 100-sheet stapling
- Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more
- Downloadable apps to help you work faster and smarter
- Multiple i-Options to suit the needs of your workflow
- EPEAT Gold-certified, low power consumption to cut costs
- Mobile printing support (AirPrint, Google Cloud Print Classic, NFC)

\*May not be available at time of launch.

## bizhub 308e

### MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER

Ideal for growing businesses, the bizhub 308e is a powerful, affordable monochrome MFP with superior Simitri® HD image quality and fast 30 ppm print/copy output. Optional dual scanning brings information into your workflow fast and numerous finishing options provide plenty of flexibility for in-house production.

#### SYSTEM OVERVIEW

<b>System memory</b>	4 GB (when UK-211 is installed)
<b>System hard disk</b>	250 GB Standard
<b>Interface</b>	10-BASE-T / 100-BASE-TX / 1000-BASE-T Ethernet, USB 2.0
<b>Network protocols</b>	TCP/IP (IPv4/IPv6), FTP, SMB v2, SMTP, WebDAV
<b>Frame types</b>	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
<b>Document feeder (optional)</b>	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163gsm Reversing automatic document feeder or dual scan document feeder available
<b>Printable paper size</b>	<b>Scanning/Copying:</b> up to 11" x 17" <b>Printing:</b> up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max.: 11.75" x 47.25"
<b>Printable paper weight</b>	52-300 gsm
<b>Paper input capacity</b>	<b>Standard:</b> 1,150 sheets / <b>Max.:</b> 6,650 sheets
<b>Tray 1</b>	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
<b>Tray 2</b>	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
<b>PC-115 Paper feed cabinet (optional)</b>	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
<b>PC-215 Paper feed cabinet (optional)</b>	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
<b>Large capacity tray PC-415 (optional)</b>	2,500 sheets / 8.5" x 11" / 52-256 gsm
<b>Large capacity tray LU-302 (optional)</b>	3,000 sheets / 8.5" x 11" / 52-256 gsm
<b>Manual bypass</b>	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
<b>Automatic duplexing</b>	5.5" x 8.5" to 12" x 18" / 52-256 gsm
<b>Finishing modes</b>	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet
<b>Output capacity</b>	<b>Max. with finisher:</b> 3,200 sheets <b>Max. without finisher:</b> 250 sheets
<b>Stapling (optional)</b>	<b>Max.:</b> 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
<b>Stapling output capacity</b>	<b>Max.:</b> 1,000 sheets
<b>Tri-fold (optional)</b>	Up to 3 sheets
<b>Tri-fold capacity</b>	<b>Max.:</b> 30 sheets (tray)
<b>Booklet (optional)</b>	<b>Max.:</b> 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
<b>Booklet output capacity</b>	<b>Max.:</b> 100 sheets (tray)
<b>Copy/print volume</b>	<b>Max.:</b> 150,000 pages/month <sup>1</sup>
<b>Toner lifetime</b>	25,000 pages
<b>Imaging unit lifetime</b>	265,000 pages / 600,000 pages (Drum/Developer)
<b>Power consumption</b>	120 V / 60 Hz, less than 1.5 kW (system)
<b>System dimensions</b>	24.2" x 27" x 38" (W x D x H)
<b>System weight</b>	Approx. 168 lbs

#### PRINTER SPECIFICATIONS

<b>Print resolution</b>	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
<b>PDL</b>	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
<b>Operating systems</b>	Windows (x32 / x64): Vista 7 / 8.1 / 10 Windows Server (x32 / x64): 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> / 2016 <sup>3</sup> Macintosh OS X 10.7 or later Linux / Unix / Citrix
<b>Printer fonts</b>	80 PCL Latin, 137 PostScript 3
<b>Print functions</b>	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

#### COPIER SPECIFICATIONS

<b>Copying process</b>	Electrostatic laser copy, tandem, indirect
<b>Toner system</b>	Simitri HD Polymerized Toner
<b>Print speed (8.5" x 11")</b>	Up to 30 ppm (portrait)
<b>Print speed (11" x 17")</b>	Up to 15 ppm (portrait)
<b>Autoduplex speed (8.5" x 11")</b>	Up to 30 ppm (portrait)
<b>1st copy out time</b>	4.8 seconds
<b>Warm-up time</b>	Approx. 20 seconds <sup>2</sup>
<b>Copy resolution</b>	600 x 600 dpi
<b>Gradations</b>	256 gradations
<b>Multi-copy</b>	1-9,999
<b>Original format</b>	Up to 11" x 17"
<b>Magnification</b>	25-400% in 0.1% steps, auto zooming
<b>Copy functions</b>	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

#### SCANNER SPECIFICATIONS

<b>Scan speed</b>	<b>B&amp;W / Color:</b> up to 160 opm with optional DF-704
<b>Scan resolution</b>	<b>Max.:</b> 600 x 600 dpi
<b>Scan modes</b>	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
<b>File formats</b>	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
<b>Scan destinations</b>	2,100 (shared with fax), LDAP support
<b>Scan functions</b>	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

#### FAX SPECIFICATIONS

<b>Fax</b>	Super G3 (optional)
<b>Transmission</b>	Analog, Internet Fax, Color i-Fax, IP-Fax
<b>Resolution</b>	<b>Max.:</b> 600 x 600 dpi (ultra-fine)
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Modem</b>	Up to 33.6 Kbps
<b>Destinations</b>	2,100 (single + group)
<b>Functions</b>	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs

#### USER BOX SPECIFICATIONS

<b>Storable documents</b>	<b>Max.:</b> 3,000 documents or 10,000 pages
<b>Type of user boxes</b>	Public Personal (with password or authentication) Group (with authentication)
<b>Type of system boxes</b>	Secure print, encrypted PDF, fax receipt, fax polling, annotation
<b>User box functionality</b>	Reprint, combination, download, sending (email/FTP/SMB and fax), copy box-to-box

## SYSTEM FEATURES

<b>Security</b>	ISO 15408 EAL <sup>4</sup> IEEE 2600.1 <sup>4</sup> IP filtering and port blocking SSL2, SSL3 and TSL1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt Print user data encryption Copy protection (Copy Guard, Password Copy) optional
<b>Accounting</b>	Up to 1,000 user accounts Active Directory support (user name + password + email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
<b>Software</b>	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

<sup>2</sup> Warm-up time may vary depending on the operating environment and usage.

<sup>3</sup> Supports x64 only.

<sup>4</sup> Certification pending.



## COMPONENTS AND OPTIONS

<b>AU-102 Biometric authentication</b>	Finger vein scanner
<b>AU-205H Universal ID card reader*</b>	Various ID card technologies
<b>AU-211 CA/PIV solution</b>	Requires WT-506 Working Table
<b>DF-629 Document feeder</b>	Reversing automatic document feeder, capacity 100 originals
<b>DF-704 Document feeder</b>	Dual scan automatic document feeder, capacity 100 originals
<b>DK-510 Copier desk</b>	Provides storage space for print media and other materials
<b>Dynamag magnetic stripe card reader</b>	Requires WT-506 Working Table
<b>EK-608 USB I/F kit</b>	USB keyboard connection
<b>EK-609 USB I/F kit</b>	USB keyboard connection, Bluetooth
<b>External keyboard</b>	External USB keyboard
<b>FK-514 Fax board</b>	Super G3 fax, digital fax functionality
<b>FK-515 Fax board</b>	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
<b>FS-533 Staple finisher</b>	50-sheet stapling, 500 sheets max. output
<b>FS-536 Staple finisher</b>	50-sheet stapling, 3,200 sheets max. output (requires RU-513)
<b>FS-536SD Booklet finisher</b>	50-sheet staple finisher, 20-sheet booklet finisher, 2,200 sheets max. output (requires RU-513)
<b>HD-524 Hard disk</b>	Hard disk mirroring, 250 GB
<b>JS-506 Job separator</b>	Separation for fax output, etc.
<b>KH-102 Keyboard holder</b>	To place USB keyboard
<b>KP-101 10-Key pad</b>	For use instead of touchscreen
<b>LK-102 v3 PDF enhancements</b>	PDF/A, PDF encryption, digital signature
<b>LK-104 v3</b>	Provides voice guidance functions
<b>LK-105 v4</b>	Searchable PDF
<b>LK-106</b>	Supports native barcode printing
<b>LK-107</b>	Supports native Unicode printing
<b>LK-108</b>	Supports native OCR A and B font printing
<b>LK-110 v2</b>	Generates various file formats incl. DOCX, XLSX and combines LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
<b>LK-111 ThinPrint® Client</b>	Print data compression for reduced network impact
<b>LU-302 Large capacity unit</b>	3,000 sheets / 8.5" x 11" / 52-256 gsm
<b>MK-730 Mount kit</b>	Banner paper guide
<b>MK-735 Mount kit</b>	Installation kit for ID card reader
<b>MK-742 Mount kit</b>	Installation kit for FK-515 fax board
<b>OC-511 Original cover</b>	Cover required if no document feeder is installed
<b>OT-506 Output tray</b>	Output tray use instead of finisher
<b>PC-115 Universal tray</b>	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
<b>PC-215 Universal tray</b>	2 x 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
<b>PC-415 Large capacity tray</b>	2,500 sheets / 8.5" x 11" / 52-256 gsm
<b>PK-519 Punch kit for FS-533</b>	2/3-hole punching, autoswitching
<b>PK-520 Punch kit for FS-536</b>	2/3-hole punching, autoswitching
<b>RU-513 Relay unit</b>	Required for the FS-536 / FS-536SD
<b>SC-508 Security kit</b>	Copy guard function
<b>SP-501 Stamp unit</b>	Added fax stamp capability kit
<b>UK-211 Memory expansion</b>	2 GB memory expansion, required for most i-options, registered overlay and concurrent use of web browser and certain other functions, including stamp print, watermark, date/time print, header/footer, image overlay and management number
<b>UK-212 Wireless LAN</b>	Wireless LAN to network connector
<b>WT-506 Working table</b>	Authentication device placement

\*May not be available at time of launch.



© 2019 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.