



bizhub[®] 368e

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER

Up to 36 ppm print/copy output to keep pace with rising demands

Optional dual scanning up to 160 originals per minute

Large 9" color display with quick tablet-like touchscreen interface

3rd-party software integration with standard web browser

Built-in Emperon[®] print system, universal printer drivers

Simitri[®] HD polymerized toner for high-resolution imaging

Standard 250 GB HDD for on-board document storage

Meets ISO 15408 and IEEE 2600.1 Security standards*

Standard web browser

Power-saving design with quick recovery from sleep mode

6,650-sheet maximum capacity, tab printing support, carbon-copy printing

Advanced authentication, secure print release, remote firmware updates

Multiple bypass tray and detachable paper feed trays improve paper handling

Finishing options for 80-page booklet-making, up to 100-sheet stapling

Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more

Downloadable apps to help you work faster and smarter

Multiple i-Options to suit the needs of your workflow

EPEAT Gold-certified, low power consumption to cut costs

Mobile printing support (AirPrint, Google Cloud Print Classic, NFC)

*May not be available at time of launch.

bizhub 368e

MONOCHROME MID-VOLUME MULTIFUNCTION PRINTER

Ideal for growing businesses, the bizhub 368e is a powerful, affordable monochrome MFP with superior Simitri® HD image quality and fast 36 ppm print/copy output. Optional dual scanning brings information into your workflow fast and enhanced touch screen simplicity never slows you down.

SYSTEM OVERVIEW

System memory	4 GB (when UK-211 is installed)
System hard disk	250 GB Standard
Interface	10-BASE-T / 100-BASE-TX / 1000-BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), FTP, SMB v2, SMTP, WebDAV
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder (optional)	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163gsm Reversing automatic document feeder or dual scan document feeder available
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
PC-115 Paper feed cabinet (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
PC-215 Paper feed cabinet (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray PC-415 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet
Output capacity	Max. with finisher: 3,200 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 175,000 pages/month ¹
Toner lifetime	25,000 pages
Imaging unit lifetime	270,000 pages / 600,000 pages (Drum/Developer)
Power consumption	120 V / 60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 38" (W x D x H)
System weight	Approx. 168 lbs

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
PDL	PCL6 (XL 3.0), PCL5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32 / x64): 7 / 8.1 / 10 Windows Server (x32 / x64): 2008 / 2008 R2 ³ / 2012 ³ / 2016 ³ Macintosh OS X 10.7 or later Linux / Unix / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri HD Polymerized Toner
Print speed (8.5" x 11")	Up to 36 ppm (portrait)
Print speed (11" x 17")	Up to 18 ppm (portrait)
Autoduplex speed (8.5" x 11")	Up to 36 ppm (portrait)
1st copy out time	4.5 seconds
Warm-up time	Approx. 20 seconds ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

SCANNER SPECIFICATIONS

Scan speed	B&W / Color: up to 160 opm with optional DF-704
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

FAX SPECIFICATIONS

Fax	Super G3 (optional)
Transmission	Analog, Internet Fax, Color i-Fax, IP-Fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs

USER BOX SPECIFICATIONS

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication) Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (email/FTP/SMB and fax), copy box-to-box

SYSTEM FEATURES

Security	ISO 15408 EAL ⁴ IEEE 2600.1 ⁴ IP filtering and port blocking SSL2, SSL3 and TLS1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt Print user data encryption Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts Active Directory support (user name + password + email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

² Warm-up time may vary depending on the operating environment and usage.

³ Supports x64 only.

⁴ Certification pending.



COMPONENTS AND OPTIONS

AU-102 Biometric authentication	Finger vein scanner
AU-205H Universal ID card reader	Various ID card technologies
AU-211 CA/PIV solution*	Requires WT-506 Working Table
DF-629 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-704 Document feeder	Dual scan automatic document feeder, capacity 100 originals
DK-510 Copier desk	Provides storage space for print media and other materials
Dynamag magnetic stripe card reader	Requires WT-506 Working Table
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection, Bluetooth
External keyboard	External USB keyboard
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output (requires RU-513)
FS-536SD Booklet finisher	50-sheet staple finisher, 20-sheet booklet finisher, 2,200 sheets max. output (requires RU-513)
HD-524 Hard disk	Hard disk mirroring, 250 GB
JS-506 Job separator	Separation for fax output, etc.
KH-102 Keyboard holder	To place USB keyboard
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3 PDF enhancements	PDF/A, PDF encryption, digital signature
LK-104 v3	Provides voice guidance functions
LK-105 v4	Searchable PDF
LK-106	Supports native barcode printing
LK-107	Supports native Unicode printing
LK-108	Supports native OCR A and B font printing
LK-110 v2	Generates various file formats incl. DOCX, XLSX and combines LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111 ThinPrint® Client	Print data compression for reduced network impact
LU-302 Large capacity unit	3,000 sheets / 8.5" x 11" / 52-256 gsm
MK-730 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OC-511 Original cover	Cover required if no document feeder is installed
OT-506 Output tray	Output tray use instead of finisher
PC-115 Universal tray	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
PC-215 Universal tray	2 x 500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
PC-415 Large capacity tray	2,500 sheets / 8.5" x 11" / 52-256 gsm
PK-519 Punch kit for FS-533	2/3-hole punching, autoswitching
PK-520 Punch kit for FS-536	2/3-hole punching, autoswitching
RU-513 Relay unit	Required for the FS-536 / FS-536SD
SC-508 Security kit	Copy guard function
SP-501 Stamp unit	Added fax stamp capability kit
UK-211 Memory expansion	2 GB memory expansion, required for most i-Options, registered overlay and concurrent use of web browser and certain other functions, including stamp print, watermark, date/time print, header/footer, image overlay and management number
UK-212 Wireless LAN	Wireless LAN to network connector
WT-506 Working table	Authentication device placement

*May not be available at time of launch.



© 2019 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.