

bizhub C4050i





CUSTOMER BENEFITS



Intuitive operability Operate the bizhub like a

smartphone or tablet with fully customized user interface



Mobile connectivityPrint anytime from anywhere with Konica Minolta's innovative mobile technologies



Security

Secure network integration, data encryption, HDD overwrite, and advanced user authentication



Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive $applications \, port folio \,$



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance, and remote setup

OPTIONS



PDF enhancements LK-102v3

OCR text recognition LK-105v4

Barcode fonts

Unicode fonts LK-107

OCR A and B fonts LK-108

Document converter pack LK-110v2

ThinPrint® client LK-111






LEGEND Mandatory option Option This option can only be installed with the respective option

above it







FINISHING FUNCTIONALITIES





Duplex

Corner stapling (offline)

bizhub C4050i Datasheet

DESCRIPTIONS

$FNH\Delta$	NCED	FFΔTI	IRFS

LK-102v3 PDF Enhancements	PDF/A (1b); PDF encryption; digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint client	Print data compression for reduced network impact
LK-116 Antivirus	Bitdefender ® antivirus provides real time scanning
	of all in-/outcoming data

CONNECTIVITY	
FK-517 Fax board	Super G3 fax, digital fax functionality (Standard)
EK-608 USB I/F kit	USB keyboard connection
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
AU-102 Biometric authenticaton	Finger vein scanner
AU-205H	Various ID card technologies
MK-P08 Mount kit	Installation kit for AU-205H

OTHERS

WT-P03 Working table	Authentication device placement	
KP-102 10-Key pad	For use instead of touchscreen	
KH-P02 Keyboard holder	To place USB keyboard	
MEDIA INPUT		
PF-P21 Paper tray	500 sheets, 8.5" x 11" or 8.5" x 14", 60-90 gsm	
PF-P25 Height adjustment unit	To achieve comfortable height for operation	
DK-P05 Copier desk	Provides storage space for print media and other materials	
MEDIA OUTPUT		
FS-P04 Off-line stapler	20-sheet off-line stapling	

TECHNICAL SPECIFICATIONS

SYSTEM SPECIFICATIONS

Panel size/resolution	10.1" / 1024 x 600
System memory (standard/max)	5 GB
Solid State Drive	256 GB (standard)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP;
	HTTP(S); AppleTalk; Bonjour
Automatic document feeder (standard)	Up to 80 originals; 5.8" x 8.3" to 8.5" x 14"; 50–128 gsm;
	Dualscan ADF
Paper input capacity (standard/max)	600 sheets / 1,600 sheets
Paper tray input (standard)	1x 500 sheets; 3.9" x 5.8" to 8.5" x 11.7";
	custom sizes; 60–210 gsm
Paper tray input (optional)	2x 500 sheets; 8.5" x 11" or 8.5" x 14"; custom sizes; 60–90 gsm
Manual bypass	100 sheets; 3.5" x 8.8" to 8.5" x 14"; Custom sizes; 60–210 gsm
Automatic duplexing	5.8" x 8.3" to 8.5" x 14"; 60-210 gsm
Finishing modes (optional)	Group; Sort; Staple (offline)
Output capacity (standard)	Max. 250 sheets
Copy/print volume (monthly)	Max. ¹ 120,000 pages
Toner lifetime	Black up to 13,000 pages
	CMY up to 9,000 pages
Imaging unit lifetime	Black up to 200,000 pages (imaging unit)
	CMY up to 100,000 pages (imaging unit)
Power consumption	110–120 V / 60 Hz; Less than 1.45 kW
System dimension (W x D x H)	18.5" x 20.8" x 22.5" (without options)
System weight	Approx. 86 lb. (without options)

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Print Speed letter (mono/color)	Up to 42/42 ppm
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10
	(32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2;
	Windows Server 2016; Windows Server 2019;
	Macintosh OS X 10.10 or later; Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android);
	Konica Minolta Mobile Print (iOS/Android/Windows 10 Mobile);
	Mobile Authentication and Pairing (iOS/Android);
	WiFi Direct

SCANNER SPECIFICATIONS

Scan speed (mono/color)	Up to 45/45 ipm in simplex
	Up to 90/90 ipm in duplex
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV;
	Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF;
	XPS; Compact XPS; PPTX
	Optional: Searchable PDF; PDF/A 1a and 1b;
	Searchable DOCX/PPTX/XLSX
Scan destinations	2,100 (single + group); LDAP support

COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	Simitri® HD polymerised toner
Copy/print speed letter (mono/color)	Up to 42/42 ppm
Autoduplex Speed letter (mono/color)	Up to 42/42 ppm
1st copy out time letter	4.8/5.4 sec.
Warm-up time	Approx. 13 sec. in mono; 15 sec. in color ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	3.9" x 8.8" to 8.5" x 14"; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS (STANDARD)

Fax standard	Super G3
Fax transmission	Analog; i-Fax; Color i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication);
	Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling
SYSTEM FEATURES	
Security Functions (standard)	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2 network
	communication; IPsec support; IEEE 802.1x support;
	User authentication; Authentication log; Secure print; Kerberos;
	Hard disk overwrite (8 standard types); Hard disk data encryption
	(AES 256); Memory data auto deletion; Confidential fax receipt;
	Print user data encryption
Security Functions (optional)	Antivirus realtime scanning (Bitdefender®)
Accounting (standard)	Up to 1,000 user accounts; Active Directory support (user name +
	password + e-mail + smb folder); User function access definition
Accounting Functions (optional)	Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (Android/iOS)
Software	PageScope Net Care Device Manager; PageScope Data Admin-
	istrator; PageScope Box Operator; PageScope Web Connection;
	Print Status Notifier; Driver Packaging Utility; Log Management
	Utility

¹ Maximum monthly copy/print volume supported under standard vendor supplied service. Defines the upper end of the expected customer volume for the device. Customers should consider multiple machines if average monthly volume approaches duty cycle on a continual basis.

- All specifications refer to letter-size paper of 80 gsm weight.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
- particular page size (6% coverage of letter). The actual life of each consumable will vary depending on use and other $printing\ variables\ including\ page\ coverage,\ page\ size,\ media\ type,\ continuous\ or\ intermittent\ printing,\ ambient$ temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.























² Warm-up time may vary depending on the operating environment and usage