



## **bizhub® C759**

### **COLOR HIGH-VOLUME MULTIFUNCTION PRINTER**

- Up to 75 ppm print/copy output to keep pace with rising demands
- Standard dual scanning handles up to 240 originals per minute
- High capacity 300-sheet document feeder
- Large 10.1" color display with quick tablet-like touchscreen interface
- Scan-to-email and FTP, scan-to-me, scan-to-home convenience
- Built-in Emperon® print system, universal printer drivers
- Simitri® HD polymerized toner for high-resolution imaging
- Standard 250 GB HDD for on-board document storage
- Web browser with 4 GB of memory
- ISO 15408 and IEEE 2600.1 security standards

- Power-saving design with quick recovery from sleep mode
- 6,650-Sheet maximum capacity, tab printing support, carbon-copy printing
- Advanced authentication, secure print release, remote firmware updates
- Multiple bypass tray and detachable paper feed trays improve paper handling
- Finishing options for 80-page booklet-making, up to 100-sheet stapling
- Options for 2/3-hole punch, tri-fold, z-fold, post-insertion and more
- Downloadable apps to help you work faster and smarter
- Multiple i-Options to suit the needs of your workflow
- EPEAT Gold-certified, low power consumption to cut costs
- Mobile printing support (AirPrint, Google Cloud Print Classic, NFC)

# bizhub C759

## COLOR HIGH-VOLUME MULTIFUNCTION PRINTER

Superior color, spectacular speed and simple touch-and-swipe operation make the bizhub C759 an ideal document solution for high-volume applications. Output speeds of 65 ppm in color and 75 ppm in B&W plus duplex scanning at up to 240 opm keep work flowing — and you'll have powerful, scalable options to increase your productivity and help control your costs.

### SYSTEM OVERVIEW

<b>System memory</b>	4 GB
<b>System hard disk</b>	250 GB Standard
<b>Interface</b>	10-BASE-T / 100-BASE-TX / 1,000-BASE-T Ethernet, USB 2.0
<b>Network protocols</b>	TCP/IP (IPv4/IPv6), SMB v2, LPD, IPP, SNMP, HTTP
<b>Frame types</b>	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
<b>Dual scan document feeder</b>	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35-210 gsm
<b>Printable paper size</b>	<b>Scanning/Copying:</b> up to 11" x 17" <b>Printing:</b> up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max.: 11.75" x 47.25"
<b>Printable paper weight</b>	52-300 gsm
<b>Paper input capacity</b>	<b>Standard:</b> 3,650 sheets / <b>Max.:</b> 6,650 sheets
<b>Tray 1</b>	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
<b>Tray 2</b>	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
<b>Tray 3*</b>	1,500 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
<b>Tray 4*</b>	1,000 sheets / 8.5" x 11", 5.5" x 8.5", 4" x 6" / 52-256 gsm
<b>Large capacity tray LU-205 (optional)</b>	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
<b>Large capacity tray LU-303 (optional)</b>	3,000 sheets / 8.5" x 11" / 52-256 gsm
<b>Manual bypass</b>	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
<b>Automatic duplexing</b>	5.5" x 8.5" to 12" x 18" / 52-256 gsm
<b>Finishing modes</b>	Offset, group, sort, staple, punch, half-fold, z-fold, tri-fold, post-insertion, booklet
<b>Output capacity</b>	<b>Max. with finisher:</b> 3,300 sheets <b>Max. without finisher:</b> 250 sheets
<b>Stapling (optional)</b>	<b>Max.:</b> 100 sheets or 94 sheets + 2 cover sheets (up to 209 gsm)
<b>Stapling output capacity</b>	<b>Max.:</b> 1,000 sheets
<b>Tri-fold (optional)</b>	Up to 3 sheets
<b>Tri-fold capacity</b>	<b>Max.:</b> 30 sheets (tray)
<b>Booklet (optional)</b>	<b>Max.:</b> 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
<b>Booklet output capacity</b>	<b>Max.:</b> 100 sheets (tray)
<b>Copy/print volume</b>	<b>Max.:</b> 300,000 pages / month <sup>1</sup>
<b>Toner lifetime</b>	<b>Black:</b> 48,900 pages / <b>CMY:</b> 33,200 pages
<b>Imaging unit lifetime</b>	<b>Black:</b> 300,000 pages / 1,200,000 pages (Drum/Developer) <b>CMY:</b> 200,000 pages
<b>Power consumption</b>	120 V / 60 Hz, less than 2.1 kW (system)
<b>System dimensions</b>	25.5" x 31.5" x 45.5" (W x D x H)
<b>System weight</b>	Approx. 487 lb

\* Paper size changes for trays 3 and 4 must be done by an authorized Konica Minolta service technician.

### COPIER SPECIFICATIONS

<b>Copying process</b>	Electrostatic laser copy, tandem, indirect
<b>Toner system</b>	Simitri™ HD Polymerized Toner
<b>Print speed (8.5" x 11")</b>	<b>B&amp;W / Color:</b> up to 75 / 65 ppm (Portrait)
<b>Print speed (11" x 17")</b>	<b>B&amp;W / Color:</b> up to 37 / 33 ppm (Portrait)
<b>Autoduplex speed (8.5" x 11")</b>	<b>B&amp;W / Color:</b> up to 75 / 65 ppm (Portrait)
<b>1st copy out time</b>	<b>B&amp;W:</b> 3.6 sec. / <b>Color:</b> 4.9 sec.
<b>Warm-up time</b>	<b>B&amp;W:</b> approx. 22 sec. / <b>Color:</b> 35 sec.
<b>Copy resolution</b>	600 x 600 dpi
<b>Gradations</b>	256 gradations
<b>Multi-copy</b>	1-9,999
<b>Original format</b>	Up to 11" x 17"
<b>Magnification</b>	25-400% in 0.1% steps, auto zooming
<b>Copy functions</b>	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, color mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

### PRINTER SPECIFICATIONS (STANDARD)

<b>Print resolution</b>	1,800 (equivalent) x 600 dpi, 1,200 x 1,200 dpi
<b>PDL</b>	PCL6 (XL 3.0), PCL5e/c, PostScript 3 (ver. 3016), XPS
<b>Operating systems</b>	Windows (x32 / x64): 7 / 8 / 10 Windows Server (x32 / x64): 2008 / 2008 R2 <sup>3</sup> / 2012 <sup>3</sup> / 2016 <sup>3</sup> Macintosh OS X 10.8 or later Linux / Unix / Citrix
<b>Printer fonts</b>	80 PCL Latin, 137 PostScript 3
<b>Print functions</b>	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

### PRINTER SPECIFICATIONS (OPTIONAL)

<b>Print controller</b>	Embedded Fiery IC-418 (VI-510 required)
<b>Memory/HDD</b>	4 GB / 250 GB
<b>PDL</b>	PostScript 3 (ver. 3019) PCL 6 / 5c
<b>Operating systems</b>	Windows (x32 / x64): 7 / 8 / 10 Macintosh OS X 10.7 or later

### SCANNER SPECIFICATIONS

<b>Scan speed</b>	<b>B&amp;W / Color:</b> up to 240 ipm
<b>Scan resolution</b>	<b>Max.:</b> 600 x 600 dpi
<b>Scan modes</b>	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
<b>File formats</b>	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
<b>Scan destinations</b>	2,100 (shared with fax), LDAP support
<b>Scan functions</b>	Annotation (text/time/date) for PDF, up to 400 job programs, real-time scan preview

### FAX SPECIFICATIONS

<b>Fax</b>	Super G3 (optional)
<b>Transmission</b>	Analog, Internet fax, Color i-Fax, IP-Fax
<b>Resolution</b>	<b>Max.:</b> 600 x 600 dpi (ultra-fine)
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Modem</b>	Up to 33.6 Kbps
<b>Destinations</b>	2,100 (single + group)
<b>Functions</b>	Polling, time shift, PC-fax, receipt to confidential box, receipt to Email/FTP/SMB, up to 400 job programs

### USER BOX SPECIFICATIONS

<b>Storable documents</b>	<b>Max.:</b> 3,000 documents or 10,000 pages
<b>Type of user boxes</b>	Public Personal (with password or authentication) Group (with authentication)
<b>Type of system boxes</b>	Secure print, encrypted PDF, fax receipt, fax polling, annotation
<b>User box functionality</b>	Reprint, combination, download, sending (Email/FTP/SMB and fax), copy box-to-box

## SYSTEM FEATURES

<b>Security</b>	ISO 15408 EAL3 <sup>4</sup> IEEE 2600.1 <sup>4</sup> IP filtering and port blocking SSL2, SSL3 and TLS 1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt Print user data encryption Copy protection (Copy Guard, Password Copy) optional
<b>Accounting</b>	Up to 1,000 user accounts Active Directory support (user name + password + Email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
<b>Software</b>	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

<sup>2</sup> Warm-up time may vary depending on the operating environment and usage.

<sup>3</sup> Supports x64 only.

<sup>4</sup> Certification pending.

## COMPONENTS AND OPTIONS

<b>AU-102 Biometric authentication</b>	Finger vein scanner
<b>AU-205H Universal ID card reader</b>	Various ID card technologies
<b>AU-211</b>	Requires WT-506 Working Table
<b>CAC/PIV solution*</b>	
<b>EK-610 USB I/F kit</b>	USB keyboard connection
<b>EK-611 USB I/F kit</b>	USB keyboard connection, Bluetooth
<b>FK-516 Fax board</b>	Super G3 fax, digital fax functionality
<b>FK-515 Fax board</b>	Super G3 fax, digital fax functionality, lines 3 & 4 support (requires MK-742)
<b>FS-536 Staple finisher</b>	50-sheet stapling, 3,200 sheets max. output
<b>FS-536SD Booklet finisher</b>	50-sheet staple finisher, 20-sheet booklet finisher, 2,500 sheets max. output
<b>FS-537 Staple finisher</b>	100-sheet stapling, 3,200 sheets max. output
<b>FS-537SD Booklet finisher</b>	100-sheet stapling, 20-sheet booklet finisher, 2,500 sheets max. output
<b>HD-524 Hard disk</b>	Backup HDD
<b>IC-418 Fiery image controller</b>	Embedded image controller for graphics-intensive applications
<b>JS-602 Job separator for FS-537</b>	Separation for fax output, etc.
<b>Keyboard</b>	External keyboard (requires KH-102)
<b>KH-102 Keyboard holder</b>	To place USB keyboard
<b>KP-101 10-Key pad</b>	For use instead of touchscreen
<b>LK-102 v3</b>	PDF/A, PDF encryption, digital signature
<b>LK-104 v3</b>	Provides voice guidance functions
<b>LK-105 v4</b>	Searchable PDF
<b>LK-106</b>	Supports native barcode printing

## COMPONENTS AND OPTIONS (CONTINUED)

<b>LK-107</b>	Supports native Unicode printing
<b>LK-108</b>	Supports native OCR A and B font printing
<b>LK-110 v2</b>	Generates various file formats incl. DOCX, XLSX and combines LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
<b>LK-111</b>	ThinPrint® Client data compression for reduced network impact
<b>LU-205 Large capacity unit</b>	2,500 sheets / 8.5" x 11" to 12" x 18" / 52-256 gsm
<b>LU-303 Large capacity unit</b>	3,000 sheets / 8.5" x 11" / 52-256 gsm
<b>MK-715 Mount kit</b>	Banner paper guide
<b>MK-735 Mount kit</b>	Installation kit for ID card reader
<b>MK-742 Mount kit</b>	Installation kit for FK-515 fax board
<b>OT-508 Output tray</b>	Output tray used instead of finisher
<b>PI-507 Post inserter for FS-537</b>	Cover insertion, post finishing
<b>PK-520 Punch kit for FS-536</b>	2/3-hole punching, autoswitching
<b>PK-523 Punch kit for FS-537</b>	2/3-hole punching, autoswitching
<b>RU-515 Relay unit</b>	Required for FS-537/FS-537SD and FS-536/FS-536SD
<b>SC-508 Security kit</b>	Copy Guard function (2x required)
<b>SK-602 Staple kit</b>	Added stapling functionality kit
<b>SP-501 Stamp unit</b>	Added fax stamp capability kit
<b>UK-212 Wireless LAN</b>	Wireless LAN to network connector
<b>UK-501 Multi-feed detection kit</b>	Detects multi-feeding in the document feeder
<b>VI-510 Interface kit for IC-418</b>	Fiery controller interface card
<b>WT-506 Working table</b>	Authentication device placement
<b>WT-513 Upright Working Table</b>	Required to mount the control panel in an upright position, can also be used to hold authentication devices
<b>ZU-609 Z-fold unit for FS-537</b>	Z-fold for 11" x 17" prints

\* May not be available at time of launch.







© 2019 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.